

IKA

designed for scientists



HS 501 digital

/// Data Sheet

Low profile laboratory shaker with large mounting surface and load capacity of up to 15 kg.

- Infinitely variable speed control from 0-300 rpm
- Digital display
- Orbital diameter 30 mm
- Ideal for all lying vessels, e.g. separating funnels
- Continuous operation (endless) even under extreme loads
- Timer function
- Attachments are not included in delivery, please order separately

www.ika.com

Subject to technical changes





designed for scientists

- Integrated USB and RS 232 interface

Technical Data

Type of movement	reciprocating
Shaking stroke [mm]	30
Permissible shaking weight (incl. attachment) [kg]	15
Motor rating input [W]	70
Motor rating output [W]	19
Permissible ON time [%]	100
Speed range [rpm]	0 - 300
Speed display	7 segment LED
Timer	yes
Timer display	scale
Time setting range [min]	1 - 55
Operating mode	timer and continuous operation
Dimensions (W x H x D) [mm]	505 x 120 x 585
Weight [kg]	26
Permissible ambient temperature [°C]	5 - 50
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	yes
USB interface	yes
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	74
Fuse	2x T4A 250V