



ULTRA-TURRAX® Tube Drive

/// Data Sheet

Unique and universal dispersing, stirring, homogenizing and grinding system with sealable disposable sample tubes. Protection and security for: Infectious sample materials, toxic substances, high-odor substances under defined conditions (time, energy, volume).

For research purposes only! Not suitable for diagnostic use (in accordance with the IVD Directive).

- Disperse, stir, homogenize and grind using a single drive unit
- No possibility of cross-contamination









designed for scientists

- Sealable disposable sample tubes
- No cleaning required
- High level of user safety
- Suitable for individual use and use in series
- Gamma-sterilized tubes
- Tubes with pierceable membrane covers
- Tubes with 2 15 ml and 15 50 ml
- Reproducible tests
- Patented

Application areas: Human medicine, pathology, veterinary medicine, animal hygiene institutes, Foodstuffs testing laboratories, Toxicology, Medical research, Pharmaceutical research, Biological research, Tumour biology, Chemistry, Cosmetics











designed for scientists

Technical Data

Motor rating input [W]	20	
Motor rating output [W]	17	
Speed display	scale	
Speed range [rpm]	300 - 6000	
Viscosity max. [mPas]	5000	
Speed deviation [%]	10	
Speed adjustment	stepless	
Noise without element [dB(A)]	50	
Process type	batch	
Dimensions (W x H x D) [mm]	100 x 40 x 160	
Weight [kg]	0.75	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 20	
Voltage [V]	100 - 240	
Frequency [Hz]	50/60	
Power input [W]	20	
DC Voltage [V=]	24	
Current consumption [mA]	800	



